

AL-WB24-100-3

galley solutions
worldwide

Water Boiler



Aerolux Limited Aircraft Galley Equipment Manufacturers
Chorley Road, Blackpool, Lancashire FY3 7XQ, England
Tel +44 (0)1253 396670 Fax +44 (0)1253 300074
Email info@aerolux.co.uk • sales@aerolux.co.uk
www.aerolux.co.uk



AL-WB24-100-3

- The 2 litre rapid [Water Boiler](#) features high performance and reliability, low maintenance and ease of use.
- Designed for long life, the boiler includes temperature and pressure devices to ensure safe and consistently high standards of performance.
- Aluminium and stainless steel establish a rugged integral construction.
- The Unit mounts on a Standard Coffee Maker Mounting Rail and can be easily removed and reinstalled from the galley without the use of special tools.
- A precision spigot alignment bush ensures accurate positioning of electrical and water connections.

Characteristics

Power Supply

115/200 V AC 360-800 Hz 3 Phase

Boiler Capacity 2 Litres

Heating Power 2700 Watts

Initial Heat up 4 Minutes

Boiler Safety Temp 90 °C

| | |
|--------------|-----------------|
| Height | 165mm (6.5") |
| Width | 158mm (6.2") |
| Depth | 367mm (14.4") |
| Empty Weight | 5.5kg (12.1lbs) |

Performance

Water Inlet Pressure 24-50 psi

Operational Range

Ambient Temperature

15-35°C (cabin temperature)

Altitude

0 to 8000ft (cabin pressure)

Documentation:

ATA / iSpec 2200 CMM

Release:

EASA Form 1 or Certificate of Conformity (COC)* model dependant

*EASA Form 1 can be provided by a DOA to POA Arrangement depending on commercial contract. Cost applicable.

Interface details

Electrical Connector

CA-3106R16S-1PF80

Water Connector

Self-sealing (Hansen) 2-KL F16

Mounting Attachment to Galley

Standard Coffee Maker Mounting Rail

Caution: Do not use the information contained in this document to perform installation design as this data is subject to change.