

Dependable Brewers for Pressurized Water System





44931 Falcon Place Sterling, VA 20166 USA Tel: +1 703.471.8600 Fax: +1 703.481.5007

www.tiaproducts.com

sales@tiaproducts.com







FEATURES

- » Microprocessor controlled
- » Positive lockdown feature
- » Non-pressurized water tank, NO vent valve required
- » Creates NO backpressure to the galley water system
- » "Eveready Brew" NO recovery time
- » Rail mounted for easy installation and removal
- » Hot water dispenser
- » Sealed membrane switch panel with tactile feedback
- » Health Monitoring System Display
- » Brew counter and operating time for maintenance recordkeeping
- » Brew tray to accommodate regular and large pillow pack
- » Warmer pad automatically turns OFF when carafe is removed
- » Solid-state relays and single heater for increased reliability
- » Easy component access for maintenance
- » Wild frequency (360-800 Hz)

OPTIONS

- » Tea function
- » Rear or Sump drain
- » ATLAS or ARINC Standard
- » 28 Volt DC Version available

SPECIFICATIONS

Dimensions:

12.0" (H) x 6.31" (W) x 13.34" (D)

Weight:

15.25 lbs. / 6.51 kg (Dry)

Voltage / Power / Brewtime:

115 VAC 3-Phase (360-800 Hz) / 2700 W / 4 min. 28 VDC / 1200 W / 6 min.