

ENDURA[®] BEVERAGE MAKER

OFFERING GREAT TASTE & UNSURPASSED RELIABILITY

The Endura[®] Beverage Maker embodies advanced technologies and innovative features setting the industry standards for reliability, quality and value to consistently deliver rich, flavorful coffee every time.



KEY ATTRIBUTES

- Modular design for flexibility & easy maintenance
- Low cost of ownership
- Ergonomic user-centric design
- Non-contact liquid level sensing
- Backward & forward compatible
- Insulated servers maintain temperature longer

10800 Plumm Road · Lenexa, KS 66215 · USA · Phone: +1.913.338.9800 · Fax: +1.913.469.8419 · www.begalleyinserts.com



MANY PARTS. *One* PARTNER.



ADVANTAGES

- Instant recovery following brew cycle
- Aroma Control
- Proprietary brew cup design to optimize flavor
- Sump drain
- Hot water from standard faucet

OPTIONS

- Combi™ tea function
- Cold water from faucet
- Swivel faucet
- Platen heater
- Rear Drain
- Lower brew cup (70-100 grams)
- True brew-in thermal insulated server

PERFORMANCE

- 3 minute brew cycle
- Compatible with existing, non-insulated servers
- Maximum brew temperature 196°F (91°C)
- Automatic filling and draining

SAFETY

- Automatic shut off when lock disengaged
- Triple redundant temperature protection
- Pressure relief valve at 80 PSI
- Low water sensing system
- Server overflow protection
- Cool to touch insulated server

SPECIFICATIONS

SIZE:

Height: 12.00 in (304.80 mm)

Width: 6.32 in (160.53 mm)

Depth: 14.89 in (378.21 mm)

WEIGHT:

Beverage Maker – 16 lbs (7.26 kg) minimum

Mounting Rail – 2.60 lbs (1.2 kg) maximum

ELECTRICAL:

- Three-Phase
- 115 Volts AC
- 360-800 Hz
- 2745 Watts nominal
- 2760 Watts with heater pad option

